

Datasheet

CFast 3TE7 series

- High IOPS
- iSMART disk health monitoring
- iPower Guard for protecting unstable start up and shut down.
- iData Guard for abnormal power failure
- DEVSLP supported




Introduction

Innodisk CFast 3TE7 is SATA III 6.0 Gb/s flash based disk, which adopts latest SATA III NAND controller with Innodisk's exclusive L³ FW architecture. The upgraded L³ FW architecture, combining Innodisk signature 4K mapping algorithm L² FW architecture with powerful LDPC technology, makes 3TE7 series have outstanding high IOPS, better data integrity and extended lifespan through reducing the bad block number happening. Built-in thermal sensor, and iData Guard ensure data integrity and reliability of CFast 3TE7 for industrial applications.

CFast 3TE7 series

Drawing



Contact us for more information about the CFast 3TE7

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No.237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

Tel: +886-2-77033000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689

www.innodisk.com

© 2019 Innodisk Corporation.
All right reserved. Specifications are subject to change without prior notice.

20190123

(General tolerance: ±0.15mm)

Specifications

Interface	SATA III
Flash Type	3D TLC
Capacity	32GB~512GB
Max. Channels	4
Sequential R/W (MB/sec, max.)	560/330
Max. Power Consumption	1.8 W
Thermal Sensor	ST- default / WT- default
External DRAM Buffer	-
H/W Write Protect	Optional*
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	42.8X 36.4 X 3.6 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: TBD

Ordering Information

Operation Temp.	32GB	64GB	128GB	256GB	512GB
Standard Grade (0°C ~ +70°C)	DECFA-32GDK1EC1SF(W)	DECFA-64GDK1EC1DF(W)	DECFA-A28DK1EC1QF(W)	DECFA-B56DK1EC1QF(W)	DECFA-C12DK1EC1QF(W)
Industrial Grade (-40°C ~ +85°C)	DECFA-32GDK1EW1SF(W)	DECFA-64GDK1EW1DF(W)	DECFA-A28DK1EW1QF(W)	DECFA-B56DK1EW1QF(W)	DECFA-C12DK1EW1QF(W)

*H/W write protect function is optional.

(For the write protect demand, please place the order by PN: DECFA-xxxDK1Ex1x**F**W)

*S:Single channel / D: Dual channel// D: four channel

innodisk

www.innodisk.com